



EFIXR angle brackets are intended for all assemblies for the design and installation of interior and exterior joinery. EFIXR stiffener improves rigidity particularly for large models.

### FEATURES






### Material

- Galvanized steel S250GD + Z275 according to NF EN 10346.

### Benefits

- The 2 obround holes make adjustments easier.



## APPLICATIONS

### Header member



- Supporting member type:** wood, concrete, metal, PVC.
- Supported member type:** wood, concrete, metal, PVC.

### For Use With

- Frames.
- Storage cabinets.

TECHNICAL DATA

Dimensions and drill holes



References	Product Dimensions [mm]				Holes Flange A					Holes Flange B	
	A	B	C	t	Ø5	Ø6.5x45	Ø6.5x50	Ø6.5x55	Ø6.5x65	Ø5	Ø8.5x30
EFIXR553C50	50	55	30	2	4	-	-	-	-	4	-
EFIXR753C50	70	55	30	2	5	-	-	-	-	4	-
EFIXR1053C50	100	55	30	2.5	6	-	-	-	-	4	-
EFIXR1253C50	120	55	30	3	6	-	-	-	-	4	-

## INSTALLATION

### Fixing

Nail holes dia. 5 mm and obround holes width 8.5 and 6.5 mm.

#### **On wood:**

- CNA annular ring-shank nails 4.0 mm.
- Bolts.
- LAG screws.
- CSA screws dia. 5.0 mm.

#### **On concrete:**

- HIPC 8-60/20 drive anchors.

#### **On metal:**

- Bolts.
- Self-drilling screws.

### Installation

1. Approcher l'élément à fixer du support,
2. Pointer l'élément. Celui-ci peut aussi être vissé à l'aide de vis adaptées,
3. Si le support est en bois, l'équerre est aussi pointée ou vissée sur celui-ci,
4. Si le support est en béton, fixer l'équerre en respectant les préconisations de pose de l'ancrage choisi.

