

## Piston Low Noise

230V • Oil Free

### Key Features

- Silent air compressor
- Fitted thermal overload
- Only 57 dB(A)
- Oil free
- 13A plug



Order Code	Model	Motor HP	Voltage	PSI	Tank Litres	Displacement CFM	FAD CFM	Noise Level dB(A)	Dimensions mm L x W x H
1703080000	Compact 106	0.75	230	116	6	3.64	2.6	57	615 x 340 x 570

## Oil Lubricated

230V • 400V

### Key Features

- Belt Driven
- Low noise acoustic cabinet
- Heavy duty S1 electric motor
  - Slow running pumps c/w cast iron block
- Automatic stop/start control
  - Hour meter
- Reduced maintenance costs



SCS 415/200



SCS 598/300

Order Code	Model	Motor HP	Voltage	PSI	Tank Litres	Displacement CFM	FAD CFM	Noise Level dB(A)	Dimensions mm L x W x H
1680900000	SCS 415/200	3.0	230	145	200	14.0	10.5	67	1440 x 600 x 1170
1693660000	SCS 598/300	5.5	400	145	270	22.0	18.5	69	1440 x 592 x 1220
1692930000	SCS 958/300	7.5	400	145	270	28.0	23.0	66	1440 x 592 x 1220