

Generating Set

GE 3500 HBM - Petrol

Key Features

- Manual recoil
- Engine shut down for low oil level
- Sockets: 2 x 230V 16A
- Overload thermal shut off
- Battery charger 12V c.c with fuse protection
- Protective frame
- Silenced
- Portable
- Meets EC directives for noise and safety

A.C. Generation - 50Hz - Single Phase, Brushless Alternator

Output *	3.2 kVA (2.9 kW) / 230V / 13.9A
PRP single-phase power *	2.9 kVA (2.6 kW) / 230V / 12.6A
Power factor (cos)	0.9
Battery charger	12V c.c
Insulation class	H

* Output power according to ISO 8528-1

Engine - Petrol, 4-Stroke, OHV, Natural Aspirated

Model	Honda GX 200
Output *	3.7 kW (5 HP)
Cylinders / Displacement	1 / 196cm ³
Speed	3000 rpm
Fuel consumption (75% of PRP)	1.1 l/h

* Power according to SAE J1349

General Specifications

Tank capacity	3.1 litres
Running time (75% Load)	2.8 hours
IP protection degree	IP 23
Dimensions LxWxH (mm)	650 x 520 x 490
Dry weight	45 Kg
Measured acoustic power LwA (pressure LpA)*	95 dB(A) (70 dB(A)
Guaranteed acoustic power LwA (pressure LpA)*	96 dB(A) (71 dB(A) @ 7m)

* Acoustic power according to European Directive 2000/14/EC



Optional

- Earthing kit
- Moving trolley CM8
- 230V/110V



Petrol Engine



Air Cooling



Manual Recoil



Engine Shut
Down (Oil)



Sockets
230V

Order Code: 35.CJ6G6010