

Generating Set

GE 2200 BI • GE 3000 BI - Petrol

Key Features

- Inverter generator supersilenced
- Automatic voltage regulator
- Engine shut down for low oil level (oil alert)
- Sockets: 2 x 230V 13A
- Overload shut off
- Battery charger with protection
- Power-smart function
- Meets EC directives

GE 2200 BI

A.C. Generation - 50Hz - Single Phase, Brushless Alternator

Stand-by single-phase power *	2.2 kVA (2.2 kW) / 230V / 8.7A
PRP single-phase power *	1.7 kVA / 230V / 7.4A
Power factor (cos)	1
Battery charger	12V c.c.
Insulation class	H

On request other voltages and frequencies (60Hz)

* Output power according to ISO 8528-1

General Specifications

Tank capacity	3.8 litres
Running time (75% Load)	6.5 hours
IP protection degree	IP 23
Dimensions LxWxH (mm) *	520 x 350 x 430
Dry weight *	24 Kg
Measured acoustic power LwA (pressure LpA)*	67.4 dB(A) @ 7m
Guaranteed acoustic power LwA (pressure LpA)*	68 dB(A) @ 7m

* Dimensions and weight (Kg) are inclusive of all parts without wheels and towbar

GE 3000 BI

A.C. Generation - 50Hz - Single Phase, Brushless Alternator

Stand-by single-phase power *	3 kW / 230V / 13A
PRP single-phase power *	2.6 kVA / 230V / 11.3A
Power factor (cos)	1
Battery charger	12V c.c.
Insulation class	H

On request other voltages and frequencies (60Hz)

* Output power according to ISO 8528-1

General Specifications

Tank capacity	5.6 litres
Running time (75% Load)	10 hours
IP protection degree	IP 23
Dimensions LxWxH (mm) *	660 x 350 x 530
Dry weight *	38 Kg
Measured acoustic power LwA (pressure LpA)*	68 dB(A) @ 7m
Guaranteed acoustic power LwA (pressure LpA)*	70 dB(A) @ 7m

* Dimensions and weight (Kg) are inclusive of all parts without wheels and towbar



Order Code: 35.CN300011



c/w Integrated trolley with retractable handle

Order Code: 35.CJ200011