

Workhorse Belt Drive Petrol

Key Features

- · Recoil start as standard
- Offering air production where no electricity supply is available
- Cast iron blocks on all models
- Air receivers built to latest European Standards 2014/29EU
- Twin cylinder pumps
- Fitted aftercoolers
- Aerodynamic flywheels for efficient cooling
- Built & tested to latest European standards in our modern production facility in Manchester, England



3 Year Engine Warranty covered by Honda service centres throughout the UK



Order Code	HP	Tank Litres	Displacement CFM	FAD CFM		Dimensions mm L x W x H
WRP5.5HP-50S	5.5	50	15.6	11.2	Static	1100 x 375 x 690
WRP5.5HP-50P	5.5	50	15.6	11.2	Portable	1150 x 375 x 690
WRP5.5HP-150S	5.5	150	15.6	11.2	Static	1350 x 480 x 1020

Above models 10 bar maximum pressure





Order Code	HP	Tank Litres	Displacement CFM	FAD CFM		Dimensions mm L x W x H
WRP9HP-150S	9.0	150	21	16.5	Static	1350 x 480 x 1020
WRP9HPXX-150S	9.0	150	24.9	19.9	Static	1350 x 480 x 1100
WRP11HP-150S	11.0	150	29.8	23	Static	1350 x 480 x 1100

Above models 10 bar maximum pressure as standard, 12 bar available to special order Electric Start option available on 9 & 11 HP Please note battery and cables not supplied

