

Stella L

The flexible solution for a wide variety of uses: extrawide ladder is comfortable to use and safe to stand on.

Product description

- Rung depth: 30 mm
- Very light but still extremely stable.
- Outside width: 490 mm.
- Also available as a shelf-ladder.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- High strength, non-twist rung/stile connections.
- Rungs and stiles made from extruded aluminium sections.

Product features

Coating: natural

Connection Stile-Rung: flanged

Load: max. 150 kg Material: Aluminium Pitch rung/tread: 270 mm

Producttype: Flanged single ladder with rungs

Standards: EN 131 professional

Tread depth: 30 mm
Type rung/tread: serrated

Warranty: 10 years



Hints and special features

Complies with EN 131 Professional.

Product variants

Order number	Number of rungs	Overall length	Stile depth	Transport dimensions	Weight	Wide crosspiece	Working height
41511	6	1.93 m	58 mm	1.930 mm × approx. 500 mm × 60 mm	3.7 kg		2.8 m
41512	8	2.49 m	58 mm	2.480 mm × approx. 500 mm × 60 mm	4.7 kg		3.35 m
41513	10	3.05 m	58 mm	3.040 mm × approx. 500 mm × 60 mm	7.2 kg	0.8 m	3.9 m
41514	12	3.61 m	58 mm	3.600 mm × approx. 500 mm × 60 mm	8.1 kg	0.89 m	4.4 m
41515	14	4.17 m	62 mm	4.160 mm × approx. 500 mm × 65 mm	9.3 kg	0.99 m	4.95 m
41516	16	4.73 m	68 mm	4.720 mm × approx. 500 mm × 70 mm	10.5 kg	0.99 m	5.5 m
41510	18	5.29 m	73 mm	5.300 mm × approx. 500 mm × 75 mm	11.9 kg	1.09 m	6.05 m
41517	20	5.86 m	73 mm	5.850 mm × approx. 500 mm × 75 mm	13.2 kg	1.09 m	6.6 m
41518	24	6.98 m	85 mm	6.980 mm × approx. 500 mm × 85 mm	16 kg	1.2 m	7.7 m